

JP-40V



JP-120H



JP 系列無油活塞式真空泵浦特性表

型 號	電 壓 V	頻 率 Hz	馬達出力 Kw	定格電流 A	最低真空壓 mmHg	最大空氣流量 l/min	進、排氣口徑 inch	噪 音 dB	重 量 Kg
JP-40V	1Ø	50	0.24	2.7	-680	45	1/4"	56	6.8
	115V	60	0.25	2.3	-680	56		56	
	1Ø	50	0.22	1.1	-680	45	1/4"	56	6.8
	230V	60	0.21	1.0	-680	56		56	
JP-90V	1Ø	50	0.18	2.2	-685	81	1/4"	56	8.35
	115V	60	0.19	1.8	-685	90		56	
	1Ø	50	0.17	0.8	-685	81	1/4"	56	8.35
	230V	60	0.17	0.9	-685	90		56	
JP-90H	1Ø	50	0.21	2.3	-740	58	1/4"	56	8.35
	115V	60	0.23	2.3	-740	66		56	
	1Ø	50	0.16	0.7	-740	58	1/4"	56	8.35
	230V	60	0.16	0.9	-740	66		56	
JP-120V	1Ø	50	0.37	3.6	-700	100	1/4"	56	8.4
	115V	60	0.45	4.1	-700	120		56	
	1Ø	50	0.24	1.5	-700	100	1/4"	56	8.4
	230V	60	0.38	1.7	-700	120		56	
JP-120H	1Ø	50	0.27	2.8	-740	79	1/4"	56	8.4
	115V	60	0.30	2.9	-740	90		56	
	1Ø	50	0.35	1.5	-740	79	1/4"	56	8.4
	230V	60	0.35	1.7	-740	90		56	
JP-140V	1Ø	50	0.51	4.6	-700	119	1/4"	56	8.4
	115V	60	0.67	5.9	-700	143		56	
	1Ø	50	0.41	1.8	-700	119	1/4"	56	8.4
	230V	60	0.52	2.3	-700	143		56	
JP-140H	1Ø	50	0.36	3.4	-740	92	1/4"	56	8.4
	115V	60	0.44	3.9	-740	105		56	
	1Ø	50	0.36	1.7	-740	92	1/4"	56	8.4
	230V	60	0.46	2.1	-740	105		56	